In the Claims:

1 (currently amended): ~~Pressure~~ A pressure containment device comprising:

a ~~main~~ housing[[,]];

a first ~~longitudinal~~ through bore which extends through the housing and is arranged to receive a wire or cable slidingly therethrough[[,]];

at least ~~two~~ second and third spaced apart ~~transversal~~ through bores ~~intersecting~~ which extend through the housing and intersect the main bore[[,]];

~~each transversal bore carrying~~ a pair of opposing rams in each of the second and third bores[[,]]; and

~~characterized in that the first bore comprises sleeves~~ a sleeve lining which is removably positioned in the first bore and through which the wire or cable extends.

2 (currently amended): ~~Device~~ The device according to claim 1, ~~characterized in that the device includes a further bore located between two of the transversal bores, the further bore extending into the main bore~~ further comprising a fourth bore which is located between the second and third bores and which extends into the first bore.

3 (currently amended): ~~Device~~ The device according to claim 1, ~~characterized in that~~ wherein each ram comprises a front part ~~of~~ which is constructed of an elastic material.

4 (currently amended): ~~Device~~ The device according to claim 4, ~~characterized in that~~ wherein the front part includes a slot for the wire or cable.

5 (currently amended): ~~Device~~ The device according to claim 1, ~~characterized in that~~ wherein each ram comprises a front part ~~with~~ which includes a knife for cutting ~~a~~ the wire or cable ~~or wire in the first bore~~.

6 (currently amended): ~~Subsea~~ A subsea lubricator comprising:

a blowout preventer[[,]];

a tool housing; and

a grease injector assembly[[,]] which comprises a pressure containment device;

~~the grease injector assembly including a~~ the pressure containment device comprising a ~~main~~ housing, a longitudinal through bore which extends through the housing and is arranged to receive a wire or cable slidingly therethrough, at least ~~one~~ a first transversal through bore ~~intersecting~~ which extends through the housing and intersects the ~~main~~ longitudinal bore, and a first pair of rams ~~arranged~~ which are positioned in the first transversal bore.

7 (new): The device according to claim 1, wherein the sleeve lining comprises a number of individual sleeves.

8 (new): The device according to claim 2, wherein the sleeve lining comprises a first sleeve which is positioned between the second and third bores.

9 (new): The device according to claim 8, wherein the first sleeve extends between the second and fourth bores and the sleeve lining further comprises a second sleeve which extends between the third and fourth bores.

10 (new): The device according to claim 8, wherein the first sleeve comprises a port which is aligned with the fourth bore.

11 (new): The subsea lubricator according to claim 6, further comprising a sleeve lining which is removably positioned in the longitudinal bore and through which the wire or cable extends.

12 (new): The subsea lubricator according to claim 11, wherein the sleeve lining comprises a number of individual sleeves.

13 (new): The subsea lubricator according to claim 12, further comprising:

a second transversal through bore which extends through the housing and intersects the longitudinal bore; and

a second pair of rams which are positioned in the second transversal bore;

wherein the sleeve lining comprises a first sleeve which is positioned between the first and second transversal bores.

14 (new): The subsea lubricator according to claim 13, further comprising a third bore which is located between the first and second transversal bores and which extends into the longitudinal bore.

15 (new): The subsea lubricator according to claim 14, wherein the first sleeve extends between the first and third bores and the sleeve lining further comprises a second sleeve which extends between the second and third bores.

16 (new): The subsea lubricator according to claim 14, wherein the first sleeve comprises a port which is aligned with the third bore.